

Milestone Review Flysheet 2023-2024

Institution	North Carolina State University	Milestone	Critical Design Review
--------------------	---------------------------------	------------------	------------------------

Vehicle Properties	
Total Length (in)	105.43
Diameter (in)	6.17
Aspect Ratio	17.09 1
Gross Lift Off Weight (lb)	49.59
Ballast Amount (lb) / Material / Location	3.2 / Steel Nuts / RFS
Launch Vehicle Burn Out Weight (lb)	45.57
Airframe Material(s)	G12 Fiberglass
Fin Material and Thickness (in)	G10 Fiberglass, 1/8
Coupler Length(s)/Shoulder Length(s) (in)	3 (Nosecone), 4.5 (AV), 6 (AV)

Motor Properties	
Motor Brand/Designation	AeroTech L1940X
Max/Average Thrust (lb)	521.21/435.97
Total Impulse (lbf-s)	973.24
Mass Before/After Burn (oz)	8.50/4.47
Liftoff Thrust (lb)	509.05
Motor Retention Method	AeroTech Motor Retainer, RFS Centering Rings

Stability Analysis	
Center of Pressure (in. from nose)	77.9
Center of Gravity (in. from nose)	60.94
Static Stability Margin (on pad)	2.75
Static Stability Margin (at rail exit)	2.81
Max/ Avg Thrust-to-Weight Ratio	10.26/8.64
Rail Size/Type and Length (in)	1515/144
Rail Exit Velocity (ft/s)	43.01

Ascent Analysis	
Maximum Velocity (ft/s)	555.24
Maximum Mach Number	0.509
Maximum Acceleration (ft/s^2)	299.26
Target Apogee (ft)	4050
Predicted Apogee (From Sim.) (ft)	4048.67

Recovery System Properties - Overall	
Total Descent Time (s)	81.54
Total Drift in 20 mph winds (ft)	2391.81

Recovery System Properties - Energetics		
Ejection System Energetics (ex. Black Powder)		#FFF Black Powder
Energetics Mass - Drogue Chute (grams)	Primary	2.5
	Backup	3
Energetics Mass - Main Chute (grams)	Primary	4.5
	Backup	5
Energetics Mass - Other (grams) - If Applicable	Primary	N/A
	Backup	N/A

Recovery System Properties - Recovery Electronics	
Primary Altimeter Make/Model	MissleWorks RRC3
Secondary Altimeter Make/Model	Eggtimer Quasar
Other Altimeters (if applicable)	N/A
Rocket Locator (Make/Model)	Eggtimer Quasar
Additional Locators (if applicable)	Big Red Bee 900
Transmitting Frequencies (all - vehicle and payload)	420.25 MHz
	900 MHz
Describe Redundancy Plan (batteries, switches, etc.)	The Quasar tracker and dual deploy altimeter will have its own battery, and the RRC3 primary altimeter will have its own battery. Each altimeter has its own e-matches, mechanical arming switch, and two ejection charges.
Pad Stay Time (Launch Configuration)	2.9 Hr

Recovery System Properties - Drogue Parachute					
Manufacturer/Model	Fruity Chutes Classic Elliptical				
Size or Diameter (in or ft)	15 in				
Main Altimeter Deployment Setting	Apogee				
Backup Altimeter Deployment Setting	Apogee + 1 second				
Velocity at Deployment (ft/s)	0				
Terminal Velocity (ft/s)	110.13				
Recovery Harness Material, Size, and Type (examples - 1/2 in. tubular Nylon or 1 in. flat Kevlar strap)	5/8 in. Tubular Kevlar				
Recovery Harness Length (ft)	19 ft				
Harness/Airframe Interfaces	Quick links will be attached to bowline knots in the shock cord. The quick links will be attached to U-bolts on the bulkheads				
Kinetic Energy of Each Section (Ft-lbs)	Section 1	1012.74	2280.18	3274.73	N/A
	Section 2	Section 3	Section 4		

Recovery System Properties - Main Parachute					
Manufacturer/Model	Fruity Chutes Compact Elliptical; Fruity Chutes Classic Elliptical				
Size or Diameter (in or ft)	96 in ; 48 in				
Main Altimeter Deployment Setting	800 ft				
Backup Altimeter Deployment Setting	700 ft				
Velocity at Deployment (ft/s)	110.13				
Terminal Velocity (ft/s)	15.38; 15.83				
Recovery Harness Material, Size, and Type (examples - 1/2 in. tubular Nylon or 1 in. flat Kevlar strap)	5/8 in. Tubular Kevlar				
Recovery Harness Length (ft)	8.5; 9				
Harness/Airframe Interfaces	Quick links will be attached to bowline knots in the shock cord. The quick links will be attached to U-bolts on the bulkheads				
Kinetic Energy of Each Section (Ft-lbs)	Section 1	20.97	44.47	63.89	N/A
	Section 2	Section 3	Section 4		

Milestone Review Flysheet 2023-2024

Institution

North Carolina State University

Milestone

Critical Design Review

Payload

Payload	
Payload 1 (official payload)	Overview
	<p>The payload on board this year's launch vehicle is the STEMnauts Atmosphere Independent Lander, or SAIL. The goal of this payload is to safely transport four non-living passengers, known as STEMnauts, from the launch vehicle to the ground without the use of a parachute. This will be achieved by using a contra-rotating set of rotor blades powered by an electric motor. The lander will be contained within a body tube know as the deployment bay. The deployment bay will contain electronics for release and a latch that holds the SAIL in place. Upon separation from the launch vehicle, the SAIL will descend in the deployment bay, which will be under a parachute. Once RSO permission is given, an RF controlled latch will release the SAIL from the deployment bay, unfolding the rotor blades and legs and sending it into free fall. At this point, the motor will start spinning the rotor blades, generating lift to slow down the SAIL. The rotor blades will continue to operate based on pre-derived lift curves until landing. The SAIL will land in an upright orientation on the four deployed landing legs.</p>
Payload 2 (non-scored payload)	Overview
	N/A

Test Plans, Status, and Results

Ejection Charge Tests	<p>Full-scale ejection testing planned for February 15th, 2024. Ejection testing will ensure that all altimeters are functioning correctly and that the charges have been sized correctly. Black powder will be loaded into the launch-day-appropriate sections. A manual switch will be used to activate the charges. The e-matches will be connected to a 9V battery, and upon a completed circuit, the charges will detonate. If the sections fail to separate, the ejection charge size has been underestimated. If the sections separate with too much force, the ejection charge size has been overestimated. Upon either case, the ejection charge size will be increased or reduced by 0.2 g respectively and the test will be repeated until separation is deemed successful.</p>
Sub-scale Test Flights	<p>The subscale test flight took place on November 18th, 2023. During the flight, all subscale launch vehicle systems operated successfully. The simulated payload mass deployed properly and all recovery events were successful. The RF command signal was successfully recieved by the nose cone reciever during descent, making it a viable method for on-command payload release for the fullscale design. Flight data and recovery images from this launch were included in the CDR report. This flight verifies NASA SL Requirement 2.18.</p>
Vehicle Demonstration Flights	<p>The Vehicle Demonstration Flight is planned for Febraury 24th-25th, 2024. This flight will determine if all team derived and NASA requirements have been met by the launch vehicle subsystems. This will satisfy NASA SLI Requirement 2.19.1.</p>
Payload Demonstration Flights	<p>The Payload Demonstration Flight is planned for March 23rd-24th, 2024. This flight will determine if all team derived and NASA requirements have been met by the payload subysytem. This will satisfy the NASA SLI Requirement 2.19.2.</p>

Milestone Review Flysheet 2023-2024

Institution	North Carolina State University	Milestone	Critical Design Review
--------------------	---------------------------------	------------------	------------------------

Transmitter #1

Location of transmitter:	Avionics Bay		
Purpose of transmitter:	Launch Vehicle Tracking Device		
Brand	Eggtimer Rocketry	RF Output Power (mW)	100 mW
Model	Quasar	Specific Frequency used by team (MHz)	420.25 MHz
Handshake or frequency hopping? (explain)	Fixed Frequency, ID 8		
Distance to closest e-match or altimeter (in)	1 in		
Description of shielding plan:	There will be a sheet of aluminum foil added between the tracker and other recovery electronics on the sled.		

Transmitter #2

Location of transmitter:	Nose Cone Sled		
Purpose of transmitter:	Nose Cone Tracking Device		
Brand	BigRedBee	RF Output Power (mW)	250 mW
Model	BRB900	Specific Frequency used by team (MHz)	900 MHz
Handshake or frequency hopping? (explain)	Fixed Frequency, ID 8		
Distance to closest e-match or altimeter (in)	35		
Description of shielding plan:	There will be a sheet of aluminum foil added around the tracker to shield from payload electronics in nose cone.		

Transmitter #3

Location of transmitter:			
Purpose of transmitter:			
Brand		RF Output Power (mW)	
Model		Specific Frequency used by team (MHz)	
Handshake or frequency hopping? (explain)			
Distance to closest e-match or altimeter (in)			
Description of shielding plan:			

Transmitter #4

Location of transmitter:			
Purpose of transmitter:			
Brand		RF Output Power (mW)	
Model		Specific Frequency used by team (MHz)	
Handshake or frequency hopping? (explain)			
Distance to closest e-match or altimeter (in)			
Description of shielding plan:			

Milestone Review Flysheet 2022-2023

Institution

North Carolina State University

Milestone

Critical Design Review

Transmitter #5

Location of transmitter:			
Purpose of transmitter:			
Brand		RF Output Power (mW)	
Model		Specific Frequency used by team (MHz)	
Handshake or frequency hopping? (explain)			
Distance to closest e-match or altimeter (in)			
Description of shielding plan:			

Transmitter #6

Location of transmitter:			
Purpose of transmitter:			
Brand		RF Output Power (mW)	
Model		Specific Frequency used by team (MHz)	
Handshake or frequency hopping? (explain)			
Distance to closest e-match or altimeter (in)			
Description of shielding plan:			

Additional Comments

Note: The Recovery System Properties - Main Parachute section of this flysheet includes both the main parachute and the parachute connected to the nose cone. The format of the entries in that section is as follows: Main parachute entry; Nose cone parachute entry.